



# maximiser

## TAPI Specification

### Version 2.1

The following TSPI functions are supported in the **maximiser** TAPI driver with Version 2.1 software:

TSPI\_providerInit  
TSPI\_providerShutdown  
TSPI\_providerEnumDevices  
TSPI\_providerUIIdentify  
TUISPI\_providerConfig

TSPI\_lineNegotiateTSPIVersion  
TSPI\_lineGetDevCaps  
TSPI\_lineGetLineDevStatus  
TSPI\_lineGetID  
TUISPI\_lineConfigDialog

TSPI\_lineGetAddressCaps  
TSPI\_lineGetNumAddressIDs  
TSPI\_lineGetAddressID

TSPI\_lineOpen  
TSPI\_lineClose

TSPI\_lineGetCallInfo  
TSPI\_lineMakeCall  
TSPI\_lineDial  
TSPI\_lineGenerateDigits  
TSPI\_lineDevSpecificFeature

TSPI\_lineAnswer  
TSPI\_lineDrop  
TSPI\_lineAccept  
TSPI\_lineCloseCall  
TSPI\_lineGetCallAddressID

Any other functions either return LINEERR\_NOERROR or LINEERR\_OPERATIONFAILED.



SpliceCom Limited  
The Hall Business Centre, Berry Lane  
Chorleywood, Hertfordshire, WD3 5EX

Tel:01923 287700  
Fax:01923 287722  
Email:info@splicecom.com  
Website:www.splicecom.com